

INTEC Controls provides. . .

... **INTEC - CONTROLLI** *Universal Modulating
& Two-Position Motorized Zone Globe Valves*

Compatible with electric or electronic analog control,
DDC/PLC control and building automation systems, 24 VAC

**Very small sized modulating actuator for
zone globe valves**

- *Designed for globe valves*
"Superior to damper actuator/valve assembly"
- *Quiet operation*
- *Low power consumption*
- *Overload protected, synchronous bidirectional motor*



MVT./VMXT

- Control signals
 - Built-in selectable ranges:
0...10 VDC, 2...10 VDC,
1...5 VDC, 4...7 VDC,
6...9 VDC, 6...10 VDC, 8...11 VDC
 - Tri-state/3-point floating or two-position
- Positioning time 117 sec., at 60 Hz
- Direct/reverse acting selectable
- External manual valve override screw-on cap



MVT./VSXT



VMXT



VSXT

*VAV Terminal Unit Reheat
Constant Volume Terminal Reheat
Fan Coil Units
Compact AC Units
Single Zone Units*

- 1/2" to 3/4" NPT screwed connection
- Cv's for 1/2": 0.29, 0.46, 0.69,
1.16, 1.85
- Cv for 3/4": 2.89, 4.62, 6.94
- 2-way and 3-way
- 232 PSIG body rated
- High turndown ratio

*Hot & Chilled Water
Mixing & Diverting
Configurations*



MVT300

Specifications subject to change without notice. | USA 200226 | Page 1 of 1

*INTEC Controls provides compatible quality controls, peripherals and interface
devices to the HVAC Controls, Energy Management and Building Automation markets.*