





ACTUATORS

MVX / MVR (Electro-Thermal)		MVT (Motorized)			
MVX22R MVX42R	MVX52	MVT28 MVT44	MVT56 MVT57	MVT403S	MVT503S
2 Pos. 24 V; 230 V	Prop. 24 V	3 Pos. 24 V; 230 V	Prop. 24 V	3 Pos. 24 V; 230 V	Prop. 24 V
31.5 lbf (140 N)		45 lbf (200 N)		67.4 lbf (300 N)	

VALVES

ANSI 125, Threaded Valves – 0.3 to 2.9 Cvs									
VSX	2-W, brass body	1/2"-3/4"	•	•	–	–	–	–	–
VMX	3-W, brass body		•	•	–	–	–	–	–
ANSI 125, Threaded Valves – 4.6 to 6.9 Cvs									
VSX24-26	2-W, brass body	3/4"	•	•	–	–	–	–	–
VMX24-26	3-W, brass body		•	•	–	–	–	–	–
ANSI 125, Threaded Valves – 0.3 to 1.9 Cvs									
VST	2-W, brass body	1/2"	–	–	•	•	•	•	•
VMT	3-W, brass body		–	–	•	•	•	•	•
ANSI 125, Threaded Valves – 0.3 to 6.9 Cvs									
VSXT	2-W, brass body	1/2"- 3/4"	–	–	•	•	•	•	•
VMXT	3-W, brass body		–	–	•	•	•	•	•
ANSI 125, Threaded Valves – 7.3 to 20.8 Cvs									
VS.B.T	2-W, cast iron body	3/4"-2"	–	–	•	•	•*1	•*1	•*1
VMB.T	3-W, cast iron body		–	–	•	•	•*1	•*1	•*1

*1 - Use MVT403 or MVT503, push/pull long bracket



ACTUATORS

MVB (Motorized)		MVE (Motorized)		MVE-R (Motorized)		MVH (Motorized)			
MVB22 MVB26 MVB28 MVB46	MVB52 MVB56	MVE506 MVE510 MVE515 MVE522	MVE506S MVE510S MVE515S MVE522S	MVE-R MVE506R MVE515R	MVE-SR MVE506SR MVE515SR	MVH26 MVH46	MVH36 MVH56	MVH56E MVH3K	MVH56EA MVH56EC
2-3 Pos. 24 V; 230 V	Prop. 24 V	3 Pos. & Prop. 24 V	3 Pos. & Prop. 24 V, Short Bracket	3 Pos. & Prop. 24 V, Fail- Safe, Long Bracket	3 Pos. & Prop. 24 V, Fail- Safe, Short Bracket	2-3 Pos. 24 V; 230 V	Prop. pot. or VDC-mA 24 V	3 Pos. & Prop. 24 V	3 Pos. & Prop. 24 V, SR
101.2 lbf (450 N)		134.9 (600), 224.8 (1000), 337.2 (1500), 494.6 (2200)		134.9 lbf (600 N)*1, 337.2 lbf (1500 N)		337.2 lbf (1500 N)		337.2 (1500) 674.4 (3000)	157.4 lbf (700 N)

VALVES

ANSI 125, Threaded Valves – 7.3 to 46.2 Cvs												
VS.B	2-W, brass body	3/4"-2"	•	•	•w/AG52	•w/AG63	•w/AG52	•w/AG63	•w/AG62	•w/AG62	•w/AG62	•w/AG62
VMB	3-W, brass body		•	•	•w/AG52	•w/AG63	•w/AG52	•w/AG63	•w/AG62	•w/AG62	•w/AG62	•w/AG62
ANSI 125, 150, 300, Flanged Valves – Up to 578 Cvs 513 PSI for High Close-Off Pressure												
2FGB.B	ANSI 125, 2-W, cast iron body, balanced plug	2 1/2"-6"	–	–	•	–	•	–	•	•	•	•
2FSA.B	ANSI 150, 2-W, cast iron body, balanced plug	1"-3"	–	–	•	–	•	–	•	•	•	•
2FAA.B	ANSI 300, 2-W, steel body, balanced plug	1"-5"	–	–	•	–	•	–	•	•	•	•
2FAA150B	ANSI 150, 2-W, steel body, double seat	6"	–	–	•	–	•	–	•	•	•	•
2FGA200B	ANSI 125, 2-W, cast iron body, double seat	8"	–	–	•	–	•	–	•	•	•	•
ANSI 125, Flanged Valves – 4.62 to 346.8 Cvs												
3FGB	3-W, cast iron body	1"-6"	–	–	•	–	•	–	•	•	•	•

*1 - MVE506 up to 2 1/2"

